

```

No.      Time      Source      Destination      Protocol Length Info
 1023 5.397072 192.168.1.16 192.168.1.11    Modbus/TCP 65    Response: Trans: 548; Unit: 1,
Func:    3: Read Holding Registers
Frame 1023: 65 bytes on wire (520 bits), 65 bytes captured (520 bits) on interface \Device\NPF_{E77C8460-
A3FE-4A9C-81F0-498A6A5D9AA7}, id 0
  Interface id: 0 (\Device\NPF_{E77C8460-A3FE-4A9C-81F0-498A6A5D9AA7})
  Interface name: \Device\NPF_{E77C8460-A3FE-4A9C-81F0-498A6A5D9AA7}
  Interface description: Ethernet
  Encapsulation type: Ethernet (1)
  Arrival Time: Jul 7, 2020 00:06:44.095790000 Paris, Madrid (heure d'été)
  [Time shift for this packet: 0.000000000 seconds]
  Epoch Time: 1594073204.095790000 seconds
  [Time delta from previous captured frame: 0.000869000 seconds]
  [Time delta from previous displayed frame: 0.000869000 seconds]
  [Time since reference or first frame: 5.397072000 seconds]
  Frame Number: 1023
  Frame Length: 65 bytes (520 bits)
  Capture Length: 65 bytes (520 bits)
  [Frame is marked: False]
  [Frame is ignored: False]
  [Protocols in frame: eth:ethertype:ip:tcp:mbtcp:modbus]
  [Coloring Rule Name: TCP]
  [Coloring Rule String: tcp]
Ethernet II, Src: KEBA_3b:99:d1 (00:60:b5:3b:99:d1), Dst: HewlettP_d5:b4:7e (b4:b6:86:d5:b4:7e)
  Destination: HewlettP_d5:b4:7e (b4:b6:86:d5:b4:7e)
  Address: HewlettP_d5:b4:7e (b4:b6:86:d5:b4:7e)
  .... 0. .... = LG bit: Globally unique address (factory default)
  .... 0. .... = IG bit: Individual address (unicast)
  Source: KEBA_3b:99:d1 (00:60:b5:3b:99:d1)
  Address: KEBA_3b:99:d1 (00:60:b5:3b:99:d1)
  .... 0. .... = LG bit: Globally unique address (factory default)
  .... 0. .... = IG bit: Individual address (unicast)
  Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.16, Dst: 192.168.1.11
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
  0000 00.. = Differentiated Services Codepoint: Default (0)
  .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
  Total Length: 51
  Identification: 0x97ec (38892)
  Flags: 0x4000, Don't fragment
  0... .... = Reserved bit: Not set
  .1. .... = Don't fragment: Set
  ..0. .... = More fragments: Not set
  Fragment offset: 0
  Time to live: 64
  Protocol: TCP (6)
  Header checksum: 0x1f6d [validation disabled]
  [Header checksum status: Unverified]
  Source: 192.168.1.16
  Destination: 192.168.1.11
Transmission Control Protocol, Src Port: 502, Dst Port: 53640, Seq: 59, Ack: 82, Len: 11
  Source Port: 502
  Destination Port: 53640
  [Stream index: 4]
  [TCP Segment Len: 11]
  Sequence number: 59 (relative sequence number)
  Sequence number (raw): 2711463974
  [Next sequence number: 70 (relative sequence number)]
  Acknowledgment number: 82 (relative ack number)
  Acknowledgment number (raw): 2817867889
  0101 .... = Header Length: 20 bytes (5)
  Flags: 0x0018 (PSH, ACK)
  000. .... = Reserved: Not set
  ...0 .... = Nonce: Not set
  .... 0... = Congestion Window Reduced (CWR): Not set
  .... .0.. = ECN-Echo: Not set
  .... ..0. = Urgent: Not set
  .... ...1 .... = Acknowledgment: Set
  .... .... 1... = Push: Set
  .... .... .0.. = Reset: Not set
  .... .... ..0. = Syn: Not set
  .... .... ...0 = Fin: Not set
  [TCP Flags: .....AP...]
  Window size value: 7300
  [Calculated window size: 7300]
  [Window size scaling factor: -1 (unknown)]
  Checksum: 0x78fb [unverified]
  [Checksum Status: Unverified]
  Urgent pointer: 0

```

[SEQ/ACK analysis]

[This is an ACK to the segment in frame: 1022]

[The RTT to ACK the segment was: 0.000869000 seconds]

[Bytes in flight: 11]

[Bytes sent since last PSH flag: 11]

[Timestamps]

[Time since first frame in this TCP stream: 4.997917000 seconds]

[Time since previous frame in this TCP stream: 0.000869000 seconds]

TCP payload (11 bytes)

[PDU Size: 11]

Modbus/TCP

Transaction Identifier: 548

Protocol Identifier: 0

Length: 5

Unit Identifier: 1

Modbus

.000 0011 = Function Code: Read Holding Registers (3)

[Request Frame: 1022]

[Time from request: 0.000869000 seconds]

Byte Count: 2

Register 18 (UINT16): 140